

TW 5216 FD



Fazendo parte da sua vida

Feature:

- Support H.265 + .H.265 . H.264. H.264h. H.264+ . H.264b encoding,
- Support VGA, HDMI full HD output simultaneously; Support CVBS output
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, VMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP),easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- **Support XVI/AHD/TVI/CVI/CVBS/IP six signals;**
- Support intelligent analysis: Human detection, face detection



Specification:

	Model	TW 5216 FD
Interface	Preview	1/4/8/9/16
Video	Codec	H265 + .H.265 . H.264. H.264h. H.264+ . H.264b
	Monitor quality	VGA (1080P at most); HDMI (4K at most);CVBS
	Preview ability	16*5M-N@12fps (6 in 1)/16*4M-N@15fps (6 in 1)/16*1080P@15fps (XVI), default 5M-N
	Encode ability	16*5M-N@6fps (6 in 1)/16*4M-N@8fps (6 in 1)/16*1080P@8fps (XVI) , default 5M-N
	Decode ability	8*5M-N@6fps (6 in 1)/16*4M-N@8fps (6 in 1)/16*1080P@8fps (XVI) , default 5M-N
	Multi-mode input	Analog: 16*5M-N hybrid: 16*5M-N (analog) +4*1080P (network)) network: 16*1080P; 4*5M
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	8ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
	Video output	1ch HDMI
	Loop Vout	N/A
	Audio I/O	2 (Can be extended to 6ch) /1
	Alarm I/O	0 (Can be extended to 4ch) /0 (Can be extended to 1ch)
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	1*RS485, Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Support up to 2 SATA interfaces, Maximum support 8T) *For HD use over 2TB, replace the 2A DVR source with a higher power source (12V – 5A Not Included)*

General	Power supply	12V/2A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃ , Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	239mm*89mm
	Weight	248g