TW 5208 FD

Feature：

- Support H.265 encoding, ultra-low bitrates, compatible with H.264 surroundings;
- Support VGA, HDMI full HD output simultaneously; Support CVBS output
- Support ONVIF; access third party
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support web, VMS, center platform management software MYEYE, provide SDK development
- Support various mobile monitoring (iPhone, Android)
- Remote Access, With DNS (ARSP),easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP six signals
- Support intelligent analysis: Human detection, face detection



Specification：

	Model	TW 5208 FD
Interface	Preview	1/4/8/9/12
Video	Codec	H.265
	Monitor quality	VGA(1080P at most);HDMI(2K at most);CVBS
	Preview ability	8*5M-N@12fps(6 in 1)/ 8*4M-N@15fps（6 in 1）/ 8*1080P@15fps（XVI），default:5M-N
	Encode ability	8*5M-N@12fps(6 in 1)/ 8*4M-N@15fps（6 in 1）/ 8*1080P@15fps（XVI），default:5M-N
	Decode ability	8*5M-N@12fps(6 in 1)/ 8*4M-N@15fps（6 in 1）/ 8*1080P@15fps（XVI），default:5M-N
	Multi-mode input	Analog：8*5M-N hybrid：8*5M-N（analog）+4*1080P（network） Network：16*1080P；16*5M
	Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; multi-level sensitivity can be set (Limited local channel)
Audio	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	8ch BNC
	Video output	1ch VGA, 1ch HDMI, 1ch CVBS
	Loop Vout	N/A
	Audio I/O	4/1
	Alarm I/O	0/0
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	Support kinds of PTZ protocols
General	USB	2* USB 2.0 ports
	HDD	1*SATA ports (Support up to 2 SATA interfaces, Maximum support 8T) ***For HD use over 2TB, replace the 2A DVR source with a higher power source (12V – 5A Not Included)***
	Power supply	12V/2A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0℃—+55℃， Humidity:10%—90%， Atm:86kpa—106kpa
	Dimension	245mm*210mm*45mm
	Weight	960g